Missouri Department of Natural Resources



PUBLIC NOTICE

DRAFT MISSOURI STATE OPERATING PERMIT

DATE: July 16, 2004

In accordance with the state Clean Water Law, Chapter 644, RSMo, Clean Water Commission regulation 10 CSR 20-6.010, and the federal Clean Water Act, the applicants listed herein have applied for authorization to either discharge to waters of the state or to operate a no-discharge wastewater treatment facility. The proposed permits for these operations are consistent with applicable water quality standards, effluent standards and/or treatment requirements or suitable timetables to meet these requirements (see 10 CSR 20-7.015 and 7.031). All permits will be issued for a period of five years, unless noted otherwise in the Public Notice for that discharge.

On the basis of preliminary staff review and the application of applicable standards and regulations, the Missouri Department of Natural Resources (MDNR), as administrative agent for the Missouri Clean Water Commission, proposes to issue a permit(s) subject to certain effluent limitations, schedules, and special conditions. The proposed determinations are tentative pending public comment.

Persons wishing to comment on the proposed permit conditions are invited to submit them in writing to the Department of Natural Resources, Water Protection Program, P.O. Box 176, Jefferson City, Missouri 65102, ATTN: Peter Goode, Professional Engineer. Please include the permit number in all comment letters.

Comments should be confined to the issues relating to the proposed action and permit(s) and the effect on water quality. The MDNR may not consider as relevant comments or objections to a permit based on issues outside the authority of the Clean Water Commission, (see $\underline{\text{Curdt v. Mo. Clean Water Commission}}$, 586 S.W.2d 58 Mo. App. 1979).

All comments must be postmarked by August 16, 2004 or received in our office by 5:00 p.m. on August 19, 2004. The requirement of a signed document makes it impossible to accept email comments for consideration at this time. Comments will be considered in the formulation of all final determinations regarding the applications. If response to this notice indicates significant public interest, a public meeting or hearing may be held after due notice for the purpose of receiving public comment on the proposed permit or determination. Public hearings and/or issuance of the permit will be conducted or processed according to 10 CSR 20-6.020.

Copies of all draft permits and other information including copies of applicable regulations are available for inspection and copying at DNR's website, http://www.dnr.state.mo.us/wpscd/wpcp/homewpcp.htm, or at the Department of Natural Resources, Water Protection Program, 205 Jefferson Street, P.O. Box 176, Jefferson City, Missouri 65102, between the hours of 8:00 a.m. and 5:00 p.m., Monday through Friday.

| Public Notice Date: July 16, 2004 Permit Number: MO-0103331 Northeast Regional Office | | | | | | |
|---|--|--|--|--|--|--|
| FACILITY NAME AND ADDRESS NAME AND ADDRESS OF OWNER | | | | | | |
| Fulton WWTP 1025 Worsham Circle Fulton, MO 65251 | City of Fulton P.O. Box 130 Fulton, MO 65251 | | | | | |
| RECEIVING STREAM & LEGAL DESCRIPTION Stinson Creek, Sec. 21, T47N, R9W, Callaway County | TYPE OF DISCHARGE Domestic, reissuance | | | | | |

This is a re-notice of the May 9, 2003 Public Notice.

STATE OF MISSOURI

DEPARTMENT OF NATURAL RESOURCES



MISSOURI STATE OPERATING PERMIT

In compliance with the Missouri Clean Water Law, (Chapter 644 R.S. Mo. as amended, hereinafter, the Law), and the Federal Water Pollution Control Act (Public Law 92-500, 92nd Congress) as amended,

| Permit No. | MO-0103331 |
|---|---|
| Owner: Address: | City of Fulton PO Box 130, Fulton, MO 65251 |
| Continuing Authority: Address: | Same as above Same as above |
| Facility Name: Address: | Fulton WWTP 1025 Worsham Circle, Fulton, MO 65251 |
| Legal Description: Latitude/Longitude: | SE ¼, NW ¼, NE ¼, Sec. 21, T47N, R9W, Callaway County +3859125/-9155528 |
| Receiving Stream: First Classified Stream and ID: USGS Basin & Sub-watershed No.: | (Stinson Creek) (C) (Stinson Creek) (C)(00710) (10300102-270002) |
| is authorized to discharge from the faci as set forth herein: | lity described herein, in accordance with the effluent limitations and monitoring requirements |
| FACILITY DESCRIPTION | |
| See page 2 | |
| | r discharges under the Missouri Clean Water Law and the National Pollutant Discharge o other regulated areas. This permit may be appealed in accordance with Section 644.051.6 of |
| Effective Date | Stephen M. Mahfood, Director, Department of Natural Resources Executive Secretary, Clean Water Commission |
| Expiration Date MO 780-0041 (10-93) | Jim Hull, Director of Staff, Clean Water Commission |

FACILITY DESCRIPTION (continued)

Outfall #001 - POTW - SIC #4952

Oxidation ditch/sludge holding tanks/aerobic digesters/sludge is land applied

Design population equivalent is 47,500.

Design flow is 2.93 MGD.

Actual flow is 1.7 MGD.

Design sludge production is 975 dry tons/reak.

Actual sludge production is 414 dry tons/year

Outfall #002 - POTW - SIC #4952

Single cell lagoon/inflow - intiltration basin/sludge is retained in lagoon.

Design flow is 4.58 MGD.

Actual flow is dependent upon precipitation

PAGE NUMBER 3 of 9

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

PERMIT NUMBER MO-0103331

The permittee is authorized to discharge from outfall(s) with serial number(s) as specified in the application for this permit. The final effluent limitations shall become effective upon issuance and remain in effect until expiration of the permit. Such discharges shall be controlled, limited and monitored by the permittee as specified below:

| controlled, limited and monitored by the per | Tillicoo do opcoli | FINAL EFFLUENT LIMITATIONS | | MONITORING REQUIREMENTS | | | | |
|--|--------------------|----------------------------|-------------------|-------------------------|--------------------------|---------------------|--|--|
| OUTFALL NUMBER AND EFFLUENT PARAMETER(S) | UNITS | DAILY MAXIMUM | WEEKLY AVERAGE | MONTHLY AVERAGE | MEASUREMENT FREQUENCY | SAMPLE TYPE | | |
| Outfall #001 | 55 | WI O CHIVION | 7(VE)(VIOE | 1 | \ | | | |
| Flow | MGD | * | | * \ | nce/day | 24 hr. total | | |
| Biochemical Oxygen Demand ₅ ** | mg/L | | 45 | 30 | once/week (Note 1) | 24 hr. composite | | |
| Total Suspended Solids** | mg/L | | 45 | 30 | once/week (Note 1) | 24 hr. composite | | |
| Ammonia as N | mg/L | * | | * | once/month | grab | | |
| Temperature |))°C | * | | * | once/month | grab | | |
| pH - Units | SU | *** | | *** | once/day | grab | | |
| MONITORING REPORTS SHALL BE SUBMITTED MONTHLY; THE FIRST REPORT IS DUE | | | | | | | | |
| Cadmium, Total Recoverable | μg/L | * | | * | once/quarter* | ***** grab | | |
| Chromium, Total Recoverable | μg/L | * | | * | once/quarter* | ***** grab | | |
| Copper, Total Recoverable | μg/L | * | | * | once/quarter* | ***** grab | | |
| Lead, Total Recoverable | μg/L | * | | * | once/quarter* | ***** grab | | |
| Nickel, Total Recoverable | μg/L | * | | * | once/quarter* | ***** grab | | |
| Zinc, Total Recoverable | μg/L | * | | * | once/quarter* | ***** grab | | |
| Hardness | mg/L | * | | * | once/quarter* | ***** grab | | |
| MONITORING REPORTS SHALL BE SUB | MITTED QUART | TERLY; THE | FIRST REPO | ORT IS DUE | | <u>-</u> | | |
| Whole Effluent Toxicity (WET) Test | % Survival | Specia | al Condit | ion #8 | once/year | 24 hr. composite | | |
| MONITORING REPORTS SHALL BE SUB | MITTED ANNUA | ALLY; THE F | IRST REPO | RT IS DUE | | | | |
| Outfall #002 | | | | | | | | |
| Flow | MGD | * | | * | once/month | 24 hr. estimate | | |
| Biochemical Oxygen Demand₅**** mg/l | | | 45 | | once/month | grab | | |
| Total Suspended Solids**** | mg/L | | 45 | | once/month | grab | | |
| pH - Units | SU | **** | OT DEDOS | **** | once/month | grab | | |
| MONITORING REPORTS SHALL BE SUB | MILLED WONTE | <u>ILY;</u> THE FIF | KST REPOR | I IS DUE | TH | ERE SHALL BE | | |

NO DISCHARGE OF FLOATING SOLIDS OR VISIBLE FOAM IN OTHER THAN TRACE AMOUNTS.

B. STANDARD CONDITIONS

IN ADDITION TO SPECIFIED CONDITIONS STATED HEREIN, THIS PERMIT IS SUBJECT TO THE ATTACHED Parts I, II & III STANDARD CONDITIONS DATED October 1, 1980 and August 15, 1994, AND HEREBY INCORPORATED AS THOUGH FULLY SET FORTH HEREIN.

| | | PAGE NUMBER 4 of 9 | | | | | | | | |
|--|--|--------------------|-------------------|--------------------|--------------------------|------------------|--|--|--|--|
| A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS PERMIT NUMBER MO-0103331 | | | | | | | | | | |
| The permittee is authorized to discharge from | n outfall(s) with | serial number | er(s) as spec | ified in the a | pplication for this pe | ermit. The final | | | | |
| effluent limitations shall become effective upon issuance and remain in effect until expiration of the permit. Such discharges shall be controlled, limited and monitored by the permittee as specified below: | | | | | | | | | | |
| | FINAL EFFLUENT LIMITATIONS MONITORING REQUIREMENTS | | | | | | | | | |
| OUTFALL NUMBER AND EFFLUENT PARAMETER(S) | UNITS | DAILY MAXIMUM | WEEKLY AVERAGE | MONTHLY AVERAGE | MEASUREMENT FREQUENCY | SAMPLE TYPE | | | | |
| Instream Sampling (Note 2) | | | | | \ | = | | | | |
| Ammonia as N | mg/L | * | | * \ | once/month | grab | | | | |
| Temperature | °C | * | | * | once/month | grab | | | | |
| pH - Units | SU | * > | | * | once/month | grab | | | | |
| Dissolved Oxygen | mg(L) | * 5 | | * | once/month | grab | | | | |
| MONITORING REPORTS SHALL BE SUBMITTED MONTHLY; THE FIRST REPORT IS DUE THERE SHALL BE | | | | | | | | | | |
| NO DISCHARGE OF FLOATING SOLIDS O | R WISTBLE FO | AMIN OTHE | R THAN TR | ACE AMOUN | NTS. | | | | | |
| B. STANDARD CONDITIONS | | | | | | | | | | |
| IN ADDITION TO SPECIFIED CONDITIONS | STATED HER | EIN, THIS P | ERMIT IS S | UBJECT TO | THE ATTACHED P | arts I, II & | | | | |
| III STANDARD CONDITIONS DATED October 1, 1980 and August 15, 1994, AND HEREBY INCORPORATED AS | | | | | | | | | | |

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS (continued)

* Monitoring requirement only.

THOUGH FULLY SET FORTH HEREIN.

- ** This facility is required to meet a removal efficiency of 85% or more.
- *** pH is measured in pH units and is not to be averaged. The pH is limited to the range of 6.0-9.0 pH units.
- **** This facility is required to meet a removal efficiency of 65% or more.
- ***** pH is measured in pH units and is not to be averaged. The pH is to be maintained at or above 6.0 pH units.
- ***** Sample once per quarter in the months of March, June, September, and December.

Note 1 - Composite sample shall, as a minimum, consist of at least four representative grab samples in a 24 hour period with at least 2 hours between each grab sample. Note 2 - Instream samples shall be taken from Stinson Creek just above the confluence with Smith Branch.

C. SPECIAL CONDITIONS

- 1. This permit may be reopened and modified, or alternatively revoked and reissued, to:
 - (a) Comply with any applicable effluent standard or limitation issued or approved under Sections 301(b)(2)(C) and (D), 304(b)(2), and 307(a) (2) of the Clean Water Act, if the effluent standard or limitation so issued or approved:
 - (1) contains different conditions or is otherwise more stringent than any effluent limitation in the permit; or
 - (2) controls any pollutant not limited in the permit.
 - (b) Incorporate new or modified effluent limitations or other conditions, if the result of a waste load allocation study, toxicity test or other information indicates changes are necessary to assure compliance with Missouri's Water Quality Standards.
 - (c) Incorporate new or modified effluent limitations or other conditions if, as the result of a watershed analysis, a Total Maximum Daily Load (TMDL) limitation is developed for the receiving waters which are currently included in Missouri's list of waters of the state not fully achieving the state's water quality standards, also called the 303(d) list.

The permit as modified or reissued under this paragraph shall also contain any other requirements of the Clean Water Act then applicable.

Page 5 of 9
Permit No. MO-0103331

SPECIAL CONDITIONS (continued)

- 2. All outfalls must be clearly marked in the field.
- Permittee will cease discharge by connection to areawide wastewater treatment system 3. within 90 days of notice of its availability.
- Changes in Discharges of Toxic Substances

- The permittee shall notify the Director as soon as it knows or has reason to believe:

 (a) That any activity has occurred or will occur which would result in the discharge of any toxic pollutant which is not limited in the permit, if that discharge will exceed the highest of the following "notification levels:"

 - (1) One hundred micrograms per liter (100 µg/L);
 (2) Two hundred micrograms per liter (200 µg/L) for acrolein and acrylonitrile; five hundred micrograms per liter (500 µg/L) for 2,5 dinitrophenol and for 2-methyl-4, 6-dinitrophenol and one milligram per liter (1 mg/L) for
 - (3) Five (5) times the maximum concentration value reported for the pollutant in the permit application (4) The level established in Part A of the permit by the Director.
- (b) That they have begun or expect to begin to use or manufacture as an intermediate or final product of byproduct any toxic pollutant, which was not reported in the permit application.
- Report as no-discharge when a discharge does not occur during the report period. 5.

Water Quality Standards

- (a) Discharges to waters of the state shall not cause a violation of water quality standards rule under 10 CSR 20-7.031, including both specific and general criteria.
- (b) General Criteria. The following general water quality criteria shall be applicable to all waters of the state at all times including mixing zones. No water contaminant, by itself or in combination with other substances, shall prevent the waters of the state from meeting the following conditions:
 - (1) Waters shall be free from substances in sufficient amounts to cause the formation of putrescent, unsightly or harmful bottom deposits or prevent full maintenance of beneficial uses;
 - (2) Waters shall be free from oil, scum and floating debris in sufficient amounts to be unsightly or prevent full maintenance of beneficial uses;
 - (3) Waters shall be free from substances in sufficient amounts to cause unsightly color or turbidity, offensive odor or prevent full maintenance of beneficial uses;
 - (4) Waters shall be free from substances or conditions in sufficient amounts to result in toxicity to human, animal or aquatic life;
 - (5) There shall be no significant human health hazard from incidental contact with the water;
 - (6) There shall be no acute toxicity to livestock or wildlife watering;
 - (7) Waters shall be free from physical, chemical or hydrologic changes that would impair the natural biological community;
 - (8) Waters shall be free from used tires, car bodies, appliances, demolition debris, used vehicles or equipment and solid waste as defined in Missouri's Solid Waste Law, section 260.200, RSMo, except as the use of such materials is specifically permitted pursuant to section 260.200-260.247.
- Sludge and Biosolids Use For Domestic Wastewater Treatment Facilities
 - (a) Permittee shall comply with the pollutant limitations, monitoring, reporting, and other requirements in accordance with the attached permit Standard Conditions.

Page 6 of 9 Permit No. MO-0103331

C. SPECIAL CONDITIONS (continued)

(b) If sludge is not removed by a contract hauler, permittee is authorized to land apply biosolids. Permit Standard Conditions, Part III shall apply to the land application of biosolids. Permittee shall notify the department at least 180 days prior to the planned removal of biosolids. The department may require submittal of a biosolids management plan for department review and approval as determined appropriate on a case-by-case basis.

The permit as modified or reissued under this paragraph shall also contain any other requirements of the Clean Water Act then applicable.

8. Whole Effluent Toxicity (WET) tests will be conducted as follows:

| SUMMARY OF WET TESTING FOR THIS PERMIT | | | | | | | | |
|--|------------------|--------------|-----------|--|--|--|--|--|
| OUTFALL | A.E.C. FREQUENCY | SAMPLE TYPE | MONTH | | | | | |
| #001 | 100% Annually | 24 hr. comp. | September | | | | | |

- a. Test Schedule and Follow-Up Requirements
 - (1) Perform a single-dilution test in the months and at the frequency specified above.

If the test passes the effluent limit do not repeat test until the next test period. Submit results with the annual report.

If the test fails the effluent limit a multiple dilution test shall be performed within 30 days, and biweekly thereafter until one of the following conditions are met:

- (a) THREE CONSECUTIVE MULTIPLE-DILUTION TESTS PASS. No further tests need to be performed until next regularly scheduled test period.
- (b) A TOTAL OF THREE MULTIPLE-DILUTION TESTS FAIL.
- (2) The permittee shall submit a summary of all test results for the test series to the Planning Section of the WPCP, DNR, Box 176, Jefferson City, MO within 14 days of the third failed test. DNR will contact the permittee with initial guidance on conducting a toxicity identification evaluation (TIE) or toxicity reduction evaluation (TRE). The permittee shall submit a plan for conducting a TIE or TRE to the Planning Section of the WPCP within 60 days of the date of DNR's letter. This plan must be approved by DNR before the TIE or TRE is begun. A schedule for completing the TIE or TRE shall be established in the plan approval.
- a. Test Schedule and Follow-Up Requirements (continued)
 - (3) Upon DNR's approval, the TIE/TRE schedule may be modified if toxicity is intermittent during the TIE/TRE investigations. A revised WET test schedule may be established by DNR for this period.
 - (4) If a previously completed TIE has clearly identified the cause of toxicity, additional TIEs will not be required as long as effluent characteristics remain essentially unchanged and the permittee is proceeding according to a DNR approved schedule to complete a TRE and reduce toxicity. Regularly scheduled WET testing as required in part b.(1) will be required during this period.

C. SPECIAL CONDITIONS (continued)

- 8. Whole Effluent Toxicity (WET) (continued)
 - (5) In addition to the WET test summary report required in part (2), all failing test results shall be reported to DNR within 14 days of the availability of results.
 - (6) All WET test results for the reporting period shall be summarized and submitted to DNR by the end of the following October. When WET test sampling is required to run over one DMR period, each DMR report shall contain information generated during the reporting period.
 - b. PASS/FAIL procedure and effluent limitations
 - (1) To pass a single-dilution test, mortality observed in the AEC test concentration shall not be significantly different (at the 95% confidence level; p = 0.05) that that observed in the upstream receiving-water control. The appropriate statistical tests of significance will be those outlined in the most current USEPA acute toxicity manual or those specified by the MDNR.
 - (2) To pass a multiple-dilution test:
 - (a) the computed percent effluent at the edge of the zone of initial dilution (AEC) must be less than three-tenths (0.3) of the LC_{50} concentration for the most sensitive of the test organisms, or,
 - (b) all dilutions equal to or greater than the AEC must be nontoxic. Failure of one multiple-dilution test is considered an effluent limit violation.

c. Test Conditions

- (1) Test species: Ceriodaphnia dubia and fathead minnows, Pimephales promelas. Organisms used in WET testing should come from cultures reared for the purpose of conducting toxicity tests and should be cultured in a manner consistent with the most current USEPA guidelines. All test animals should be cultured as described in EPA-600/4-90/027.
- (2) Test period: 48 hours at the "Acceptable Effluent Concentration" (AEC) specified above.
- (3) When dilutions are required, upstream receiving stream water will be used as dilution water. If upstream water is unavailable or if mortality in the upstream water exceeds 10%, "reconstituted" water will be used. Procedures for generating reconstituted water will be supplied by the Department of Natural Resources (DNR).
- (4) Tests should be initiated immediately after the sample is collected, but tests must be initiated no later than 36 hours after collection.
- c. Test Conditions (continued)
 - (5) Single-dilution tests will be run with:
 - (a) Effluent at the AEC concentration;
 - (b) 100% receiving-stream water (if available), collected upstream of the outfall at a point beyond any influence of the effluent; and
 - (c) reconstituted water.
 - (6) Multiple-dilution tests will be run with:

C. SPECIAL CONDITIONS (continued)

- 8. Whole Effluent Toxicity (WET) (continued)
 - (a) 100%, 50%, 25%, 12.5%, and 6.25% effluent, unless the AEC is less than 25% effluent, in which case dilutions will be 4 times the AEC, two times the AEC, AEC, ½ AEC and ¼ AEC.
 - (b) 100% receiving-stream water (if available) collected upstream of the outfall at a point beyond any influence of the effluent; and
 - (c) reconstituted water.

(7) If reconstituted-water control mortality for a test species exceeds 10%, the entire test will be rerun.

SUMMARY OF TEST METHODOLOGY FOR WHOLE-EFFLUENT TOXICITY TESTS

Whole-effluent-toxicity test required in NPDES permits shall use the following test conditions when performing single or multiple dilution methods. Any future changes in methodology will be supplied to the permittee by the Missouri Department of Natural with Methods for Measuring the Acute Toxicity of Efflyents and Receiving Waters to

Resources (MDNR). Unless otherwise specified by MDNR procedures should be consistent Freshwater and Marine Organisms, EPA/600/4-90/027 Test conditions for Ceriodaphnia dubia: Test duration: Temperature: 26 ± 2°C Light Quality: Ambient laboratory illumination Photoperiod: 16 h light, 8 h dark Size of test versel 30 mL (minimum) Volume of test solution 15 mL (minimum) Age of test organisms <24 h old No. of animals/test 5 No. of replicates/concentration: 4 No. of organisms/concentration: 20 (minimum) Feeding regime: None (feed prior to test) Aeration: None Dilution water: Upstream receiving water; if no upstream flow, synthetic water modified to reflect effluent hardness. Mortality (Statistically significant Endpoint: difference from upstream receiving water control at $p \le 0.05$) Test acceptability criterion: 90% or greater survival in controls Test conditions for (Pimephales promelas): Test duration: 48 h Temperature: 25 ± 2 °C Ambient laboratory illumination Light Quality: Photoperiod: 16 h light/ 8 h dark Size of test vessel: 250 mL (minimum) Volume of test solution: 200 mL (minimum) Age of test organisms: 1-14 days (all same age) No. of animals/test vessel: No. of replicates/concentration: 4 (minimum) single dilution method 2 (minimum) multiple dilution method No. of organisms/concentration: 40 (minimum) single dilution method 20 (minimum) multiple dilution method Feeding regime: None (feed prior to test) None, unless DO concentration falls below 4.0 Aeration: mg/L; rate should not exceed 100 bubbles/min. Dilution water: Upstream receiving water; if no upstream flow, synthetic water modified to reflect

effluent hardness. Endpoint: Mortality (Statistically significant difference from upstream receiving water

control at $p \le 0.05$) Test Acceptability criterion: 90% or greater survival in controls Date of Fact Sheet: July 9, 2004

Date of Public Notice: July 16, 2004

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT FACT SHEET

This Fact Sheet explains the applicable regulations, rationale for development of this permit and the public participation process.

NPDES PERMIT NUMBER: MO-0103331

FACILITY NAME: Fulton WWTP

OWNER NAME: City of Fulton

LOCATION: Sec. 21, T47N, R9W, Callaway County

RECEIVING STREAM: Stinson Creek

FACILITY CONTACT PERSON: Jim Ianke TELEPHONE: (573) 642-8040

FACILITY DESCRIPTION AND RATIONALE

The City of Fulton has applied for reissuance of National Pollutant Discharge Elimination System (NPDES) permit number MO-0103331 for the wastewater treatment plant serving the City of Fulton.

The wastewater treatment plant is a publicly owned treatment works (POTW) with a design population equivalent of 47,500. Outfall #001 is the discharge point for the oxidation ditch and sludge holding tanks and has a design flow of 2.93 million gallons per day (MGD). Outfall #002 is the discharge point for a single cell lagoon that serves as an Inflow and Infiltration basin during rain events. Outfall #002 has a design flow of 4.58 MGD.

Missouri's Water Quality Standards, 10 CSR 20-7.031 defines the state's water quality objectives in terms of water uses to be maintained and criteria to protect those uses. Stinson Creek is classified for protection of livestock and wildlife watering, and aquatic life protection (limited warm-water fishery).

Effluent limitations are proposed according to the attached Water Quality Review Sheet with the exception of the metals. Data submitted by the permittee indicates Stinson Creek to be a "limited warm water fishery", therefore, we are proposing "monitoring only" for the metals.

The permit will be issued for a period of five years.

FACT SHEET Fulton WWTP MO-0103331

PUBLIC PARTICIPATION

Public comments on the proposed permit are being requested in accordance with Public Participation regulation under 10 CSR 20-6.020.

A copy of the public notice and this fact sheet are being forwarded to the applicant, the District Engineer of the U.S. Army Corps of Engineers, the U.S. Fish and Wildlife Service, the Environmental Protection Agency and the Missouri Department of Conservation. Other interested individuals may obtain a copy on request by writing to the address listed below for comment letters.

Comments should be confined to the issues relating to the proposed action and permit and their effect on water quality. The Missouri Department of Natural Resources may not consider comments or objections to a permit based on questions of zoning, location, or other non-water quality issues. See, <u>Curdt v. MO Clean Water Commission</u>, 586 S.W. 2d 58 (Mo. App. 1979).

The proposed determinations of the draft permit are tentative pending the public notice process.

Persons wishing to comment upon or object to the proposed determinations are invited to submit them in writing to: Department of Natural Resources, Water Protection and Soil Conservation Division, (Missouri Clean Water Commission), P.O. Box 176, Jefferson City, Missouri 65102, ATTN: Peter Goode, P.E., Chief, NPDES Permits and Engineering Section. Please include the permit number of the draft permit in all comment letters.

Within 30 days from the public notice date, as listed on page one, all water quality comments received will be considered in the formulation of all final determinations regarding this application. If response to the public notice indicates significant public interest, a public hearing may be held after due notice. Public hearing and/or issuance of the NPDES permit will be processed according to 10 CSR 20-6.020.

Copies of all draft permits, comments and other information are available for inspection and copying at the Department of Natural Resources, Water Protection and Soil Conservation Division, (Missouri Clean Water Commission) Water Protection Program, P.O. Box 176, 205 Jefferson Street, Jefferson City, Missouri 65102.

PERMIT REGULATIONS

The Federal Water Pollution Control Act ("Clean Water Act" Section 402 Public Law 92-500 as amended) established the National Pollutant Discharge Elimination System (NPDES) permit program. This program regulates the discharge of pollutants from point sources into the waters of the United States. All such discharges are unlawful without a permit (Section 301 of the "Clean Water Act"). After a permit is obtained, a discharge not in compliance with all permit terms and conditions is unlawful. NPDES permits in Missouri are issued by the Director of the Department of Natural Resources under an approved NPDES program, operating in accordance with federal and state laws (Federal "Clean Water Act" and "Missouri Clean Water Law" Section 644 as amended).

WATER QUALITY STANDARDS

10 CSR 20-7.031 Missouri Water Quality Standards, Missouri Department of Natural Resources (the Department) "defines the Clean Water Commission's water quality objectives in terms of water uses to be maintained and the criteria to protect those uses".

EFFLUENT LIMITATIONS

In order to protect these beneficial uses and the water quality of surface waters and groundwater, effluent limitations are being established under federal and state laws. The monitoring requirements for all parameters have been established by the Department in compliance with 10 CSR 20-7.015 Effluent Regulation.

The current Department effluent regulations 10 CSR 20-7.015 states that non-domestic waste discharges "shall meet the applicable control technology currently effective or that which will become effective during the life of the permit. Where this definition is not available or applicable the Department shall set specific parameter limitations using best engineering judgment as defined in 402(a)(1) of the Federal Clean Water Act".

STANDARD CONDITIONS

The standard conditions attached to the draft permit are applied to all NPDES permittees. They reflect requirements of federal (40 CFR 122) and state law (10 CSR 20-Chapter 6) with respect to NPDES permittee duties, responsibilities and liabilities.



Missouri Department of Natural Resource Water Protection Program NPDES Permits and Engineering Section

Water Quality Review Sheet Determination of Effluent Limits

FACILITY INFORMATION

| FACILITY TYPE/DESCRIPTION: Oxidation ditch & settling basin | |
|---|--|
| | |
| Ecoregion: Ozark Highlands 8- Digit HUC: 10300102 County: Callaway | |
| Central Irregular Plains Osage Plains Mississippi Alluvial Plains Ozark Highlands | |
| LEGAL DESCRIPTION: SE ¼, NW ¼, NE ¼, Sec. 21, T47N, R9W LATITUDE/LONGITUDE: 38°50'12.5"/91°55'52.8" | |
| WATER QUALITY HISTORY: Two effluent violations over last five years; BOD at outfall 001 in April 2002, TSS at outfall 002 in July 2000. | |
| Facility has had I & I problems, which appear to be adequately addressed with settling basin. | |
| Receiving stream is on 303d list for Biochemical Oxygen Demand and Volatile Suspended Solids | |
| because of this facility. It is a candidate for de-listing. | |

OUTFALL CHARACTERISTICS

| Outfall | DESIGN FLOW (CFS) | TREATMENT TYPE | RECEIVING WATERBODY | OTHER |
|---------|-------------------|--|---------------------|-------------------------------------|
| 001 | 4.54 | Oxidation ditch, aerobic digesters | Stinson Creek | |
| 002 | 7.1 | Single cell lagoon - infiltration basin | Stinson Creek | Located 2400 feet upstream from 001 |

RECEIVING WATERBODY INFORMATION

| WATERBODY | CLASS | 7Q10(cfs) | *Designated Uses | OTHER CHARACTERISTICS |
|---------------|-------|-----------|------------------|-----------------------|
| Stinson Creek | С | 0.0 | LWW, AOL | |

^{*}Cool Water Fishery (CLF), Cold Water Fishery (CDF), Irrigation (IRR), Industrial (IND),
Boating & Canoeing (BTG), Drinking Water Supply (DWS), Whole Body Contact Recreation (WBC),
Protection of Warmwater Aquatic Life and Human Health (AQL), Livestock & Wildlife Watering (LWW)

COMMENTS: Monitoring data indicate that facility is not significantly depressing DO in Stinson Creek. Therefore regular limits for BOD will be applicable.

MIXING CONSIDERATIONS

Mixing Zone. Approximately 1000 feet from Outfall 001 to confluence with Smith Branch [10 CSR 20-7.031(4)(A)5B(I)(a)].

Zone of Initial Dilution (Z.I.D.). Not allowed [10 CSR 20-7.031(4)(A)5B(I)(b)].

PERMIT LIMITS AND INFORMATION

| TMDL WATERSHED: | Y | W.L.A. | STUDY CONDUCTED: | Y | Disinfection Required: | N | DISINFECTION WAIVER: | NA |
|-----------------|---|----------|------------------|---|------------------------|---|----------------------|----|
| (Y OR N) | | (Y OR N) | | | (Y OR N) | | (Y, N, NA) | |

OUTFALL 001

WET TEST (Y OR N):

Y FREQUENCY:

Once/year

A.E.C. 100% LIMIT: No significant mortality

| PARAMETER | Units | Maximum Daily Limit | Average Weekly Limit | Average Monthly Limit | MONITORING FREQUENCY | SAMPLE TYPE |
|---|-------|------------------------|-------------------------|--------------------------|-------------------------|-------------|
| Flow | MGD | * | | * | Once/day | 24 hr total |
| Biochemical Oxygen Demand | mg/l | | 45 | 30 | Once/week | 24 hr comp. |
| Total Suspended Solids | mg/l | | 45 | 30 | Once/week | 24 hr comp. |
| Ammonia Nitrogen April 1 - October 31 | mg/l | 1.6** | | 0.8** | Once/month | grab |
| Ammonia Nitrogen November 1 - March 31 | mg/l | 2.9** | | 1.4** | Once/month | grab |
| Temperature | °C | * | | * | Once/month | grab |
| рН | units | (6-9) | | | Once/day | grab |
| Hardness | mg/l | * | | * | Once/quarter | grab |
| Cadmium, Total Recoverable | μg/l | 16 | | 8 | Once/quarter | grab |
| Chromium, Total Recoverable | μg/l | 71 | | 36 | Once/quarter | grab |
| Copper, Total Recoverable | μg/l | 48 | | 24 | Once/quarter | grab |
| Lead, Total Recoverable | μg/l | 33 | | 17 | Once/quarter | grab |
| Nickel, Total Recoverable | μg/l | 592 | | 295 | Once/quarter | grab |
| Zinc, Total Recoverable | μg/l | 400 | | 200 | Once/quarter | grab |

^{**} To be imposed at first upgrade or increase in capacity.

OUTFALL 002

| WET TEST (Y OR N): N FREQUENCY: A.E. | LIMIT: |
|--------------------------------------|--------|
|--------------------------------------|--------|

| PARAMETER | Units | MAXIMUM | Average | Average | Monitoring | SAMPLE TYPE |
|---------------------------|-------|-------------|--------------|---------------|------------|-------------|
| | | Daily Limit | WEEKLY LIMIT | MONTHLY LIMIT | FREQUENCY | |
| Flow | MGD | * | | * | Once/month | 24 hr |
| | | | | | | estimate |
| Biochemical Oxygen Demand | mg/l | | 45 | | Once/month | grab |
| Total Suspended Solids | mg/l | | 45 | | Once/month | grab |
| рН | units | min 6 | | | Once/month | grab |

Please report the date, time, and location for each parameter sampled along with the average daily flow (actual flow measured or estimated, not design flow). All the parameters should be sampled on the same day and within no more than a 2-hour period. If dissolved oxygen (DO) is to be sampled, sampling should take place at dawn. If discharge is contingent to storm events, rainfall should be measured every time there is a discharge.

RECEIVING WATER MONITORING REQUIREMENTS

Site S1. Stinson Creek just above confluence with Smith Branch

| Parameter(s) | Sampling Frequency | Sample Type | LOCATION |
|------------------|--------------------|-------------|---------------------------------------|
| Ammonia Nitrogen | Once/month | grab | NE ¼, SE ¼, NE ¼, Sec. 21, T47N, R9W; |
| Temperature | Once/month | grab | 38°50′12.4″/91°55′42.1″ |
| рН | Once/month | grab | |
| Dissolved Oxygen | Once/month | grab | |

DERIVATION AND DISCUSSION OF LIMITS

Outfall #001

BOD & NFR: 10CSR20-7.015(8)(B)1

pH: 10CSR20-7.015(8)(B)2

Ammonia as N: Current Ammonia as Nitrogen limits from WLA used to determine long term average (LTA). Maximum Daily (MDL) and Average Monthly (AML) limits were calculated in accordance with methods outlined in EPA/505/2-90-001.

Waste Load Allocation:

Chronic Criteria Total Ammonia (26° C, pH = 7.8): 1.2 mg/l Summer Ammonia as N Criteria: (1.2 mg/l)/1.2 = 1 mg/l

Chronic Criteria Total Ammonia (6°C, pH = 7.8): 2.1 mg/l Winter Ammonia as N Criteria: (2.1 mg/l)/1.2 = 1.75 mg/l

| Season | W.L.A | L.T.A | M.D.L. | A.M.L. |
|--------------------------------|-------|-------|--------|--------|
| Summer (April 1 - October 31) | 1 | 0.527 | 1.639 | 0.817 |
| Winter (November 1 - March 31) | 1.75 | 0.922 | 2.868 | 1.429 |

C.V. = 0.6, n = 4

Metals:

Conversions from limits for dissolved metals are in EPA 823-B-96-007. They are based on the assumption of a hardness of 100 mg/l. Currently there is no hardness data available for this facility.

| Parameter | Chronic Criteria | Chronic Total | Acute Criteria | Acute Total |
|-----------------|------------------|------------------------|----------------|------------------------|
| | (Dissolved) | Recoverable Multiplier | (Dissolved) | Recoverable Multiplier |
| Cadmium (µg/l) | 9.1 | 1.1001 | 31 | 1.059 |
| Chromium (µg/l) | 42 | 1.0395 | 62 | 1.018 |
| Copper (µg/l) | 28 | 1.0417 | 43 | 1.0417 |
| Lead (µg/l) | 16 | 1.264 | 104 | 1.264 |
| Nickel (µg/l) | 360 | 1.003 | 3200 | 1.002 |
| Zinc (µg/l) | 241 | 1.014 | 264 | 1.0225 |

Maximum Daily Limits (MDL) and Average Monthly Limits (AML) were calculated in accordance with methods outlined in EPA/505/2-90-001. Maximum daily and average monthly limits are for Total Recoverable Metals. Since 7Q10 for Stinson Creek is zero, Waste Load Allocations (WLA $_{\rm c}$ and WLA $_{\rm a}$) are equivalent to water quality standards for chronic and acute toxicities for each substance. Since metals are conservative substances, WLA $_{\rm c}$ is used for calculation.

| Parameter | W.L.A. _c | W.L.A.a | L.T.A. | M.D.L. | A.M.L. |
|-----------------|---------------------|---------|--------|--------|--------|
| Cadmium (µg/l) | 10.01 | 32.83 | 5.28 | 16.4 | 8.18 |
| Chromium (µg/l) | 43.66 | 63.12 | 23.01 | 71.56 | 35.66 |
| Copper (µg/l) | 29.17 | 44.79 | 15.37 | 47.81 | 23.83 |
| Lead (µg/l) | 20.23 | 131.48 | 10.66 | 33.16 | 16.52 |
| Nickel (µg/l) | 361.08 | 3206.4 | 190.29 | 591.8 | 294.95 |
| Zinc (µg/l) | 244.37 | 269.94 | 128.78 | 400.52 | 199.61 |

C.V. = 0.6, n = 4

Outfall #002

BOD, NFR, & pH: 10CSR20-7.015(8)(B)3a

Reviewer: Mark W Osborn

Date: 2/6/03

Unit Chief: Mohsen Dkhili

Monitoring and effluent limits contained within this document have been developed in accordance with EPA guidelines using the best available data and are believed to be consistent with Missouri's Water Quality Standards and Effluent Regulations. If additional water quality data or anecdotal information are available that may affect the recommended monitoring and effluent limits, please forward these data and information to the author.